



Changes for the Better

PLK-G1010-K2

>>> Electronically controlled sewing machine. Pneumatic type offering the possibility to use the left and the right clamp independently. 100x100 mm.



MITSUBISHI ELECTRIC EUROPE B.V.

Industrial Sewing Machines Division

29, Boulevard des Bouvets - 92741 Nanterre Cedex - France

Phone : +33 1 41 02 83 00 - Fax : +33 1 49 01 07 28

<http://www.ism.mitsubishielectric.fr> - Email : ism@mitsubishielectric.fr

PLK-G1010-K2

PLK-G1010-K2



This machine uses USB memory for pattern storage as well as an internal memory. It is equipped with an on-board touch screen for making sewing patterns and customizing parameters. Programmable presser foot height control according to the material thickness. All sewing parts and electronic components are available. Pneumatic type offering the possibility to use the left and right clamp independently.

Specifications

MODEL	PLK-G1010-K2
Stitch type	Single needle lockstitch
Sewing area	(X) 100 x (Y) 100 mm
Speed	2 800 rpm (depending on operation)
Feeding system	Intermittent or continuous
Stitch length	0.1 ~ 20.0 mm (min. resolution 0.1 mm)
Pattern storage	Internal memory or external USB
Max. number of stitches	20 000 stiches / pattern
Max. number of patterns	512 patterns (internal memory)
Scale-up / Scale down	10 ~ 200% for X and Y axis
Presser foot	Adjustment by stepping motor
Hook	Large size shuttle hook
Needle	DP x 17#18
Work holder lift	Max. 25 mm
Presser foot lift	Max. 18 mm
Pattern input	Touch screen (PLK-G-PAL)
Main driving motor	750 W direct drive
Power	220 ~ 240 V, 1 or 3 phases
Mass (kg)	133

Applications

Belt sewing, harness, straps, labels attaching etc...

